



NOTE:
 ALL DIMENSIONS ARE IN INCHES.
 DIMENSIONS IN [] ARE MM.
 *BOTTOM RAIL BRACKET CAN BE MOVED
 IF NEEDED WITHIN THE RANGE NOTED*

- NOTES:**
1. EACH RAIL SECTION SHALL HAVE A MINIMUM OF ONE RAIL BRACKET.
 2. SPACING CANNOT BE GREATER THAN 8'-0" BETWEEN RAIL BRACKETS.
 3. BRACKET LOCATION MUST BE NO CLOSER THAN 8" TO A RAIL SPLICE.
 4. SEE DRAWING C-003071 FOR RAIL AND PIT FLOOR REACTIONS.

NOTE:
 RAIL LENGTH = PIT DEPTH + TRAVEL
 + CAB I.D. HEIGHT + 4"

TOP RAIL MUST BE BETWEEN
 14" AND 90"

FOX VALLEY ELEVATOR TM
 1726 North Ballard Road
 Appleton, WI 54911
 Phone: 800-238-8739

ELEVATOR CONTRACTOR:			
JOB NAME:		ORDER NUMBER:	
EXCELEVATOR RMR RAIL LAYOUT & SHEAVE LOCATION			
DRAWN BY:	DATE:	SIGNATURE OF APPROVAL	DWG. NO. C-002828